



---

1801 Kilmonack Ln. Charlotte, NC 28270  
704-846-3737 • Fax: 704-846-3761  
www.cmtnc.com

## Silicone Flexible Sleeve

Material usages include connector sleeves for weighing applications and vibration isolation. Silicone material is FDA compliant – FDA 21 CFR 177.2600 and meets the requirements of use in contact with food and drugs according to 177.2600. Product is adhesive free.

### Material specifications

Color	White
Diameters:	2" to 14"
Hardness Shore A	60
Bellow Thickness	1 mm
End Thickness	2 mm
Elongation Break	300%
Thickness:	.030" (30 mil)
Tensil:	6000+ psi
Length:	3.5"
Temperature:	140 F continuous; 392 F intermittent

### User's responsibility:

This bulletin cannot cover all possible situations, which the user may experience during processing. Each aspect of your operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. It is your responsibility to use this information to develop appropriate work practice guidelines and employee instructional programs for your operation.

### Disclaimer of Liability:

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this material. Information contained herein is believed to be true and accurate, but all statements suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state and local laws and regulations remains the responsibility of the user.

